

# RCCN 日成SDR型密封环保阻燃线槽 Solid Wiring Duct



E306674 E306674 RoHS REACH 94V-0

产品材质:采用低卤素硬质PVC料制成,环保无污染,不含铅等有毒物。
产品认证:美国UL:E306674 欧洲CE,欧洲环保RoHS,REACH。
防火等级:UL94V-0,低烟微卤,遇火不燃烧,防火性及绝缘性特佳。
产品构造:由槽底及槽盖组成。
颜　　色 :灰色,白色,蓝色,黑色（可定制其它颜色，有起订量要求）
工作温度 :静态-40°C持续高温至65°C,短时间可达85°C。
使用方法:先将底槽固定,将所要配的线装入槽内,盖上槽盖即可。
产品特性 : 1.反扣式槽盖与槽体设计组合後绝不脱落,且接合面平滑,不割伤手及擦损附近配线。
2.配线槽65°C内不易断裂,变形,变色,装配省时便利。
更多选择:量大可按需求生产所需规格或定制长度.例:SDR8080(L=1.8M)

Solid wall design fully encloses cables providing maximum protection and aesthetics
Certificates:UL:E306674 CE:EN50085 RoHS,REACH。
Made of rigid PVC
Work Temperature:-40°C to 65°C
UL94 Flammability Rating of V-0
Supplied without mounting holes
Available color:gray.white.blue.black and other special colors




本系列产品均可制成面带孔规格。
Comment：gray is the common color, other color need more MOQ


单位/Unit:mm

| 型号 Item No. | | | | 宽×高 High X width W×H | 电线容量 以2.0平方计算 Wire capability/2.0sp | 标准长度 Standard Length |
|---|---|---|---|---|---|---|
| 灰色Gray RAL7030 | 白色White RAL9016 | 蓝色Blue RAL5015 | 黑色Black RAL9005 | | | |
| SDR1616 | SDR1616W | SDR1616E | SDR1616B | 16×16 | 3~10pcs | 每支2米 含槽底槽盖 Pcs/Branch 2M Including truning and lids |
| SDR2516 | SDR2516W | SDR2516E | SDR2516B | 25×16 | 5~15pcs | |
| SDR4016 | SDR4016W | SDR4016E | SDR4016B | 40×16 | 15~30pcs | |
| SDR1520 | SDR1520W | SDR1520E | SDR1520B | 15×20 | 8~12pcs | |
| SDR2020 | SDR2020W | SDR2020E | SDR2020B | 20×20 | 10~20pcs | |
| SDR4020 | SDR4020W | SDR4020E | SDR4020B | 40×20 | 20~30pcs | |
| SDR1525 | SDR1525W | SDR1525E | SDR1525B | 15×25 | 5~15pcs | |
| SDR2025 | SDR2025W | SDR2025E | SDR2025B | 20×25 | 5~15pcs | |
| SDR2525 | SDR2525W | SDR2525E | SDR2525B | 25×25 | 10~25pcs | |
| SDR3025 | SDR3025W | SDR3025E | SDR3025B | 30×25 | 12~28pcs | |
| SDR4025 | SDR4025W | SDR4025E | SDR4025B | 40×25 | 20~25pcs | |
| SDR5025 | SDR5025W | SDR5025E | SDR5025B | 50×25 | 20~30pcs | |
| SDR1530 | SDR1530W | SDR1530E | SDR1530B | 15×30 | 8~15pcs | |
| SDR2030 | SDR2030W | SDR2030E | SDR2030B | 20×30 | 25~35pcs | |
| SDR2530 | SDR2530W | SDR2530E | SDR2530B | 25×30 | 25~35pcs | |
| SDR3030 | SDR3030W | SDR3030E | SDR3030B | 30×30 | 25~35pcs | |
| SDR4030 | SDR4030W | SDR4030E | SDR4030B | 40×30 | 30~40pcs | |
| SDR5030 | SDR5030W | SDR5030E | SDR5030B | 50×30 | 40~50pcs | |
| SDR6030 | SDR6030W | SDR6030E | SDR6030B | 60×30 | 50~60pcs | |
| SDR2233 | SDR2233W | SDR2233E | SDR2233B | 22×33 | 15~25pcs | |
| SDR3333 | SDR3333W | SDR3333E | SDR3333B | 33×33 | 30~40pcs | |
| SDR2035 | SDR2035W | SDR2035E | SDR2035B | 20×35 | 30~40pcs | |
| SDR3535 | SDR3535W | SDR3535E | SDR3535B | 35×35 | 35~45pcs | |
| SDR5035 | SDR5035W | SDR5035E | SDR5035B | 50×35 | 40~60pcs | |
| SDR1540 | SDR1540W | SDR1540E | SDR1540B | 15×40 | 20~25pcs | |
| SDR2040 | SDR2040W | SDR2040E | SDR2040B | 20×40 | 20~25pcs | |
| SDR2540 | SDR2540W | SDR2540E | SDR2540B | 25×40 | 20~25pcs | |
| SDR3540 | SDR3540W | SDR3540E | SDR3540B | 35×40 | 50~60pcs | |
| SDR4040 | SDR4040W | SDR4040E | SDR4040B | 40×40 | 60~70pcs | |
| SDR6040 | SDR6040W | SDR6040E | SDR6040B | 60×40 | 100~115pcs | |
| SDR8040 | SDR8040W | SDR8040E | SDR8040B | 80×40 | 120~135pcs | |
| SDR10040 | SDR10040W | SDR10040E | SDR10040B | 100×40 | 120~135pcs | |
| SDR12040 | SDR12040W | SDR12040E | SDR12040B | 120×40 | 140~165pcs | |
| SDR2545 | SDR2545W | SDR2545E | SDR2545B | 25×45 | 20~25pcs | |
| SDR3345 | SDR3345W | SDR3345E | SDR3345B | 33×45 | 40~55pcs | |
| SDR4545 | SDR4545W | SDR4545E | SDR4545B | 45×45 | 60~70pcs | |
| SDR6545 | SDR6545W | SDR6545E | SDR6545B | 65×45 | 110~120pcs | |

# RCCN 日成SDR型密封环保阻燃线槽 Solid Wiring Duct

| 型号 Item No. | | | | 宽×高 High X width W×H | 电线容量 以2.0平方计算 Wire capability/2.0sp | 标准长度 Standard Length |
|---|---|---|---|---|---|---|
| 灰色Gray RAL7030 | 白色White RAL9016 | 蓝色Blue RAL5015 | 黑色Black RAL9005 | | | |
| SDR2050 | SDR2050W | SDR2050E | SDR2050B | 20×50 | 20~30pcs | 每支 2米 含槽底槽盖 Pcs/Branch 2M Including truning and lids |
| SDR2550 | SDR2550W | SDR2550E | SDR2550B | 25×50 | 20~30pcs | |
| SDR3050 | SDR3050W | SDR3050E | SDR3050B | 30×50 | 25~40pcs | |
| SDR3550 | SDR3550W | SDR3550E | SDR3550B | 35×50 | 40~60pcs | |
| SDR4050 | SDR4050W | SDR4050E | SDR4050B | 40×50 | 60~70pcs | |
| SDR4550 | SDR4550W | SDR4550E | SDR4550B | 45×50 | 70~80pcs | |
| SDR5050 | SDR5050W | SDR5050E | SDR5050B | 50×50 | 80~90pcs | |
| SDR5550 | SDR5550W | SDR5550E | SDR5550B | 55×50 | 85~95pcs | |
| SDR6050 | SDR6050W | SDR6050E | SDR6050B | 60×50 | 100~120pcs | |
| SDR7550 | SDR7550W | SDR7550E | SDR7550B | 75×50 | 150~170pcs | |
| SDR8050 | SDR8050W | SDR8050E | SDR8050B | 80×50 | 160~180pcs | |
| SDR10050 | SDR10050W | SDR10050E | SDR10050B | 100×50 | 200~250pcs | |
| SDR12555 | SDR12555W | SDR12555E | SDR12555B | 125×55 | 220~270pcs | |
| SDR2060 | SDR2060W | SDR2060E | SDR2060B | 20×60 | 5~45pcs | |
| SDR2560 | SDR2560W | SDR2560E | SDR2560B | 25×60 | 40~50pcs | |
| SDR3060 | SDR3060W | SDR3060E | SDR3060B | 30×60 | 60~80pcs | |
| SDR3560 | SDR3560W | SDR3560E | SDR3560B | 35×60 | 65~85pcs | |
| SDR4060 | SDR4060W | SDR4060E | SDR4060B | 40×60 | 100~115pcs | |
| SDR4560 | SDR4560W | SDR4560E | SDR4560B | 45×60 | 110~125pcs | |
| SDR5060 | SDR5060W | SDR5060E | SDR5060B | 50×60 | 120~135pcs | |
| SDR6060 | SDR6060W | SDR6060E | SDR6060B | 60×60 | 20~135pcs | |
| SDR8060 | SDR8060W | SDR8060E | SDR8060B | 80×60 | 180~210pcs | |
| SDR10060 | SDR10060W | SDR10060E | SDR10060B | 100×60 | 240~290pcs | |
| SDR11060 | SDR11060W | SDR11060E | SDR11060B | 110×60 | 50~300pcs | |
| SDR12060 | SDR12060W | SDR12060E | SDR12060B | 120×60 | 260~320pcs | |
| SDR15060 | SDR15060W | SDR15060E | SDR15060B | 150×60 | 300~360pcs | |
| SDR2565 | SDR2565W | SDR2565E | SDR2565B | 25×65 | 40~50pcs | |
| SDR3365 | SDR3365W | SDR3365E | SDR3365B | 33×65 | 40~70pcs | |
| SDR4565 | SDR4565W | SDR4565E | SDR4565B | 45×65 | 110~120pcs | |
| SDR6565 | SDR6565W | SDR6565E | SDR6565B | 65×65 | 180~200pcs | |
| SDR7265 | SDR7265W | SDR7265E | SDR7265B | 72×65 | 190~210pcs | |
| SDR2575 | SDR2575W | SDR2575E | SDR2575B | 25×75 | 140~170pcs | |
| SDR3575 | SDR3575W | SDR3575E | SDR3575B | 35×75 | 160~190pcs | |
| SDR5075 | SDR5075W | SDR5075E | SDR5075B | 50×75 | 180~210pcs | |
| SDR7575 | SDR7575W | SDR7575E | SDR7575B | 75×75 | 200~240pcs | |
| SDR10075 | SDR10075W | SDR10075E | SDR10075B | 100×75 | 250~290pcs | |
| SDR2580 | SDR2580W | SDR2580E | SDR2580B | 25×80 | 100~120pcs | |
| SDR3080 | SDR3080W | SDR3080E | SDR3080B | 30×80 | 110~125pcs | |
| SDR3580 | SDR3580W | SDR3580E | SDR3580B | 35×80 | 110~130pcs | |
| SDR4080 | SDR4080W | SDR4080E | SDR4080B | 40×80 | 140~160pcs | |
| SDR4580 | SDR4580W | SDR4580E | SDR4580B | 45×80 | 140~160pcs | 每支 2米 含槽底槽盖 Pcs/Branch 2M Including truning and lids |
| SDR5080 | SDR5080W | SDR5080E | SDR5080B | 50×80 | 160~180pcs | |
| SDR5580 | SDR5580W | SDR5580E | SDR5580B | 55×80 | 160~180pcs | |
| SDR6080 | SDR6080W | SDR6080E | SDR6080B | 60×80 | 180~210pcs | |
| SDR8080 | SDR8080W | SDR8080E | SDR8080B | 80×80 | 240~290pcs | |
| SDR10080 | SDR10080W | SDR10080E | SDR10080B | 100×80 | 260~350pcs | |
| SDR12080 | SDR12080W | SDR12080E | SDR12080B | 120×80 | 280~380pcs | |
| SDR14080 | SDR14080W | SDR14080E | SDR14080B | 140×80 | 350~450pcs | |
| SDR25100 | SDR25100W | SDR25100E | SDR25100B | 25×100 | 110~160pcs | |
| SDR33100 | SDR33100W | SDR33100E | SDR33100B | 33×100 | 130~165pcs | |
| SDR40100 | SDR40100W | SDR40100E | SDR40100B | 40×100 | 130~175pcs | |
| SDR50100 | SDR50100W | SDR50100E | SDR50100B | 50×100 | 220~250pcs | |
| SDR60100 | SDR60100W | SDR60100E | SDR60100B | 60×100 | 240~290pcs | |
| SDR70100 | SDR70100W | SDR70100E | SDR70100B | 70×100 | 250~340pcs | |
| SDR75100 | SDR75100W | SDR75100E | SDR75100B | 75×100 | 260~350pcs | |
| SDR80100 | SDR80100W | SDR80100E | SDR80100B | 80×100 | 260~350pcs | |
| SDR100100 | SDR100100W | SDR100100E | SDR100100B | 100×100 | 300~400pcs | |
| SDR120100 | SDR120100W | SDR120100E | SDR120100B | 120×100 | 350~450pcs | |
| SDR150100 | SDR150100W | SDR150100E | SDR150100B | 150×100 | 400~650pcs | |
| SDR100130 | SDR100130W | SDR100130E | SDR100130B | 100×130 | 350~450pcs | |
| SDR150130 | SDR150130W | SDR150130E | SDR150130B | 150×130 | 400~500pcs | |
| SDR200100 | SDR200100W | SDR200100E | SDR200100B | 200×100 | 600~800pcs | |
| SDR200150 | SDR200150W | SDR200150E | SDR200150B | 200×150 | 900~1200pcs | |
| SDR200200 | SDR200200W | SDR200200E | SDR200200B | 200×200 | 1200~1600pcs | |

# RCCN 日成SDR型密封环保阻燃线槽 Solid Wiring Duct




| 特点/Features | 优点/Advantages | 益处/Benefits |
|---|---|---|
| **环保阻燃材料**<br>Rohs approved<br>Enviroment-friendly Material | **符合欧盟ROHS环保测试,**<br>**符合美国UL94V-0,良好的阻燃性**<br>Approved by EU Rohs,<br>Compliant with US UL 94V-0,good inflaming | **环保不含有铅的PVC 不会对人体健康构成危害,材料良好阻燃性,使明火自熄,在着火的情况下,保证安全**<br>Eliminates health concerns associated with PVC that contains lead |
| **防滑盖**<br>non-slip liner inside duct covers) | **安装时不容易滑盖**<br>Will not slide easily when installed on duct base | **防运输振动导致滑盖　防线槽垂直安装时滑盖**<br>Cover stays in place during shipment,<br>vibration and when in a vertical orientation,eliminating rework |
| **平整的盖子设计**<br>Flush cover designGreater capacity than traditional duct designs | **比传统的设计有更大的空间**<br>**盖子与槽体齐平**<br>Cover sits flush with sidewall | **比老款装相同数量的电线表面更平整美观**<br>Can potentially use a smaller size wiring duct for same number of wires<br>Provides a neat and finished appearance |
| **四种颜色可选**<br>Four different colors | **可用于不同场合的安装要求。**<br>Suitable to different environments using | **项目对颜色有要求时选择范围更加的广泛更快的满足终端用户的需求。**<br>Can meet different customers'request in different project |
| **通过多项认证**<br>Approved by many certificates | **美国UL,加拿大CULUS, 欧盟CE ,ROHS,REACH**<br>**铁道部机车阻燃低烟认证。**<br>America UL,Canada CULUS, EuropeCE ,ROHS,REACH<br>Flamility and low smoking certificate | **满足项目应用零配件需要提供产品认证,确保产品在世界各地均可放心使用**<br>Can provide related certificates of the projects or parts need |

