ONLINE CERTIFICATIONS DIRECTORY

ZODZ.E306674 Positioning Devices

Page Bottom

Positioning Devices

See General Information for Positioning Devices

SHANGHAI RICHENG ELECTRONICS CO LTD

831 FENGPU AVE FENGXIAN DISTRICT 201400 SHANGHAI, CHINA

Cable ties, Cat. Nos. G80M, G90M, G100M, G120M, G140M, G150M, G160M, G200M, G250M, G300M, G120ST, G150ST, G160ST, G190ST, G200ST, G215ST, G250ST, G265ST, G280ST, G300ST, G370ST, G390ST, G430ST, G450ST, G530ST, G550ST, G635ST, G685ST, G120I, G140I, G150I, G180I, G200I, G215I, G250I, G300I, G370I, G150HD, G200HD, G250HD, G300HD, G370HD, G430HDS, G450HDS, G530HDS, G630HDS, GE430HD, G230EHD, G290EHD, G380EHD, G480EHD, G1030EHD, for indoor use not to exceed 85 ° C.

Cat. Nos. G150HDUV, G120STUV, G150STUV, G160STUV, G190STUV, G200STUV, G215STUV, G250STUV, G265STUV, G265STUV, G280STUV, G300STUV, G370STUV, G390STUV, G430STUV, G450STUV, G530STUV, G550STUV, G635STUV, G685STUV, G80MUV, G90MUV, G100MUV, G120MUV, G140MUV, G150MUV, G160MUV, G200MUV, G250MUV, G300MUV, G140IUV, G150IUV, G180IUV, G200IUV, G215IUV, G250IUV, G300IUV, G370IUV, G200HDUV, G250HDUV, G300HDUV, G370DHUV, G430HDSUV, G450HDSUV, G530HDSUV, G630HDSUV, G630HDSUV, G730EHDUV, G380EHDUV, E1030EHDUV, for indoor or outdoor use not to exceed 85 ° C.

Mountable cable ties, Cat. Nos. TCV-110M, TCV-150I, TCV-205ST, TCV-200ST, TCV-300ST, TCV-370ST, TCV-200HD, TCV-300HD, TCV-380HD, for indoor use not to exceed 85 ° C.

Cat. Nos. TCV-200STUV, TCV-300STUV, TCV-370STUV, TCV-110MUV, TCV-150IUV, TCV-205STUV, TCV-200HDUV, TCV-300DHUV, TCV-380HDUV, for indoor or outdoor use not to exceed 85 ° C.

Push mount cable ties, Cat. Nos. PWV-110M, PWV-110MA, PVW-130M, PVW-130MA, PVW-130I, PWV-130IA, PCV-150I, PWV-130ST, PWV-170ST, PWV190ST, PCV-200ST, for indoor use not to exceed 85 ° C.

Cat. Nos. PWV-110MUV, PWV-110MAUV, PWV-130MUV, PWV-130MAUV, PWV-130IUV, PWV-130IAUV, PCV-150IUV, PWV-130STUV, PWV-170STUV, PWV-190STUV, PCV-200STUV, for indoor or outdoor use not to exceed 85 ° C.

Releasable cable ties, Cat. Nos. HV-100HD, HV-120HD, HV-150HD, HV-200HD, HV-250HD, HV-300HD, HV-370HD, RCV-140I, RCV-200ST, RCV-300ST, RCV-370ST, RCV-430ST, for indoor use not to exceed 85 ° C.

Cat. Nos. HV-100HDUV, HV-120HDUV, HV-150DHUV, HV-200DHUV, HV-250HDUV, HV-300HDUV, HV-370HDUV, RCV-140IUV, RCV-200STUV, RCV-300STUV, RCV-370STUV, RCV-430STUV, for indoor or outdoor use not to exceed 85 ° C.

Marker cable ties, Cat. Nos. MCV-110, MCV-210S, MCV-200S, MCV-100, MCV1-190, MCV1-220, MCV1-270, MCV1-300, MCV1-370, MCV1-190L, MCV1-220L, MCV1-270L, MCV1-300L, MCV-370L, for indoor use not to exceed 85 ° C.

Last Updated on 2011-01-07

Questions?

Print this page

Notice of Disclaimer

Page Top

Copyright ?2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/showpage.... 2011-2-14

E306674

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

